INSTALLATION INSTRUCTIONS: Fiberglass Hood Bubble/Scoop, 1966-77 Bronco

PART#1102

CONTENTS:

- 1 Hood Bubble
- 1 106" Piece Black Welting
- 1 Pack approx. 40 Pop Rivets

James Duff Inc. The Bronco Specialists since 1967

865.938.6696 www.dufftuff.com 6609 Bronco Ln. Knoxville, TN 37921

1/1 11/06

Please read completely before beginning.

- 1. Extend the length of the carburetor air cleaner stud so that it touches the bottom of the hood.
- 2. Put a spot of paint on the extended stud and mark the hood by slowly lowering hood.
- 3. Remove the hood from vehicle and place the hood on saw horses or something similar. Drill 1/8" hole where hood is marked.
- 4. Draw circle on outside of hood 1" larger than you plan on using.
- 5. Drill 1/2" hole two places inside the circle, use saber saw to cut circle.
- 6. In order to retain the hood's strength, pop rivet the cut ends of the cross brace to the outer sheetmetal.
- 7. Center bubble on the hood approx. 1/4" forward of the windshield nozzle, or to preference. If you want to put any "breather" holes or vents in the bubble, this is the time to do so.
- 8. Loosely layout the welting around the bubble. Cut pie shaped wedges in the vinyl to allow it to bend around the corners.
- 9. Begin pop riveting 1/2" in from the edge of the bubble and approx. 4" apart.

LIMITED WARRANTY

James Duff Inc. warrants our products to the original purchaser to be free from defects in materials and workmanship. Warranty periods begin at the date of purchase and varies by product. Shocks have a limited lifetime warranty. Headers, Radiators, Suspension Products, Power Brake Boosters and Master Cylinders have a one year warranty. Adapters and soft goods such as upholstery, vinyl and rubber products have a 90 day warranty. All warranties are to the original purchaser with proof of purchase only. Such obligations under this warranty shall be limited to the repair or replacement, at JDI's discretion, of any assembly or part which upon examination by JDI proves to be defective. Any costs of removal, installation, reinstallation or freight charges are expressly excluded from this warranty. This warranty covers only manufacturers defects, and does not cover product finish or damage resulting from abuse, misuse, negligence, racing, alteration, accident or damage in transit.

All returns must be pre-authorized by JDI and accompanied with a Return Goods Authorization Number (RGA) and a dated proof of purchase. Returns must be made within 90 days of purchase, packaged sufficiently to prevent damage in shipment and sent prepaid to JDI, 6609 Bronco Ln., Knoxville, TN 37921 Returns without an RGA# will be refused. This warranty is expressly in lieu of all other warranties, expressed or implied, including the implied warranties of merchantability and fitness for use. This warranty gives you specific legal rights including other rights that vary from state to state. Some states do not allow limitations on how long an implied warranty lasts, or do not allow the exclusion of limitation of incidental or consequential damages, so the above limitations and/or exclusions may not apply to you.

INSTALLATION INSTRUCTIONS: Fiberglass Hood Bubble/Scoop, 1966-77 Bronco

PART#1102

CONTENTS:

- 1 Hood Bubble
- 1 106" Piece Black Welting
- 1 Pack approx. 40 Pop Rivets

James Duff Inc. The Bronco Specialists since 1967

865.938.6696 www.dufftuff.com 6609 Bronco Ln. Knoxville, TN 37921

1/1 11/06

Please read completely before beginning.

- 1. Extend the length of the carburetor air cleaner stud so that it touches the bottom of the hood.
- 2. Put a spot of paint on the extended stud and mark the hood by slowly lowering hood.
- 3. Remove the hood from vehicle and place the hood on saw horses or something similar. Drill 1/8" hole where hood is marked.
- 4. Draw circle on outside of hood 1" larger than you plan on using.
- 5. Drill 1/2" hole two places inside the circle, use saber saw to cut circle.
- 6. In order to retain the hood's strength, pop rivet the cut ends of the cross brace to the outer sheetmetal.
- 7. Center bubble on the hood approx. 1/4" forward of the windshield nozzle, or to preference. If you want to put any "breather" holes or vents in the bubble, this is the time to do so.
- 8. Loosely layout the welting around the bubble. Cut pie shaped wedges in the vinyl to allow it to bend around the corners.
- 9. Begin pop riveting 1/2" in from the edge of the bubble and approx. 4" apart.

LIMITED WARRANT

James Duff Inc. warrants our products to the original purchaser to be free from defects in materials and workmanship. Warranty periods begin at the date of purchase and varies by product. Shocks have a limited lifetime warranty. Headers, Radiators, Suspension Products, Power Brake Boosters and Master Cylinders have a one year warranty. Adapters and soft goods such as upholstery, vinyl and rubber products have a 90 day warranty. All warranties are to the original purchaser with proof of purchase only. Such obligations under this warranty shall be limited to the repair or replacement, at JDI's discretion, of any assembly or part which upon examination by JDI proves to be defective. Any costs of removal, installation, reinstallation or freight charges are expressly excluded from this warranty. This warranty covers only manufacturers defects, and does not cover product finish or damage resulting from abuse, misuse, negligence, racing, alteration, accident or damage in transit.

All returns must be pre-authorized by JDI and accompanied with a Return Goods Authorization Number (RGA) and a dated proof of purchase. Returns must be made within 90 days of purchase, packaged sufficiently to prevent damage in shipment and sent prepaid to JDI, 6609 Bronco Ln., Knoxville, TN 37921 Returns without an RGA# will be refused. This warranty is expressly in lieu of all other warranties, expressed or implied, including the implied warranties of merchantability and fitness for use. This warranty gives you specific legal rights including other rights that vary from state to state. Some states do not allow limitations on how long an implied warranty lasts, or do not allow the exclusion of limitation of incidental or consequential damages, so the above limitations and/or exclusions may not apply to you.